

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TICKOPUR R 60

UFI: KG10-S0GT-R00N-23NQ

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cleaning agent. Intensive cleaner for the ultrasonic bath, concentrate.
Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DR.H.STAMM GmbH Chemische Fabrik
Street: Heinrichstr. 3 – 4
Place: 12207 Berlin, GERMANY
Telephone: +49 30 76880-280
e-mail: info@dr-stamm.de
Internet: www.dr-stamm.de
Responsible Department: sdb@dr-stamm.de, Tel.: +49 30 76880-258
1.4. Emergency telephone number: 24-hours-emergency: Giftnotruf Berlin: +49 30 30686700 (german, english)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Corr. 1; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Sodium hydroxide; caustic soda

Signal word: Danger**Pictograms:****Hazard statements**

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7732-18-5	Water			80-90 %
	231-791-2			
1310-73-2	Sodium hydroxide; caustic soda			<12,5 %
	215-185-5	011-002-00-6	01-2119457892-27	
	Skin Corr. 1A; H314			
527-07-1	Sodium gluconate			<5,0 %
	208-407-7		*1	
100085-64-1	Cocobetainamido Amphopropionate			<1,0 %
	309-206-8		*	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1; H315 H319 H400			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1310-73-2	215-185-5	Sodium hydroxide; caustic soda	<12,5 %
	oral: LD50 = 2000 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		
100085-64-1	309-206-8	Cocobetainamido Amphopropionate	<1,0 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % amphoteric surfactants.

Further Information

*Polymer

*1 Exempted from registration (Annex IV listed)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

In case of inhalation of aerosols/spray mist/splash spots: Consult physician. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Do not induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

No symptoms known up to now.

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water. Foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixtureCan be released in case of fire: Nitrogen oxides (NO_x). Carbon dioxide (CO₂).**5.3. Advice for firefighters**

Special protective equipment for fire-fighters: Use appropriate respiratory protection. In case of fire and/or explosion do not breathe fumes.

Additional information

Material is not combustible. Extinguishing materials should be selected according to the surrounding area.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from unprotected people. Keep upwind. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Guide people to safety.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up**Other information**

Clean contaminated articles and floor according to the environmental legislation. Treat the assimilated material according to the section on waste disposal. Suitable absorbing material: Sand Universal binding agent. earth. Sawdust.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

It is recommended to organise all working processes in order to exclude the following: skin contact. Eye contact.

Advice on protection against fire and explosion

Product is not: Oxidizing. Flammable. Explosive.

Advice on general occupational hygiene

Do not eat, drink, smoke or sneeze at the workplace.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store only in original container.

Keep away from food, drink and animal feedingstuffs.

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 4 of 9

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1310-73-2	Sodium hydroxide; caustic soda			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Suitable material:

PE (polyethylene). Layer thickness: 0,5 mm penetration time (maximum wearing period): >=8h

CR (polychloroprenes, Chloroprene rubber). 0,5 mm penetration time (maximum wearing period): >=8h

NBR (Nitrile rubber). 0,35 mm penetration time (maximum wearing period): >=8h

Butyl rubber. FKM (Fluoroelastomer (Viton)). 0,5 mm penetration time (maximum wearing period): >=8h

Breakthrough times and swelling characteristics of the material must be taken into consideration.

Recommended protective gloves brand: Camapren 722, Manufacturer: KCL, or comparable makes from other companies.

Skin protection

Lab apron.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear, light yellow
Odour:	characteristic

Melting point/freezing point:	-15 °C
Boiling point or initial boiling point and boiling range:	100 °C

Flash point:

pH-Value (at 20 °C):

Water solubility:

(at 20 °C)

Density (at 20 °C):

Test method

non-flammable
 13,6 (conc.) 12,3 (1 %) DGF H-III 1
 complete miscible

1,160 g/cm³ DIN 12791

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 5 of 9

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

not Explosive.

Oxidizing properties

not oxidizing.

Other safety characteristics

Sublimation point:

n.a.

Softening point:

n.a.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Exothermic reactions with: acid, concentrated.

10.2. Chemical stability

The product is chemically stable under normal ambient conditions.

10.3. Possibility of hazardous reactions

None, in case of proper use.

10.5. Incompatible materials

acid, concentrated. Reducing agents.

10.6. Hazardous decomposition products

None, in case of proper use.

Further information

Do not mix with other products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda				
	oral	LD50 2000 mg/kg	rat		
100085-64-1	Cocobetainamido Amphopropionate				
	oral	LD50 >2000 mg/kg	Ratte	OECD 401	
	dermal	LD50 >2000 mg/kg	Ratte	OECD 402	

Irritation and corrosivity

Causes severe skin burns and eye damage. (On basis of test data)

Causes serious eye damage. (On basis of test data)

Irritant effect on the skin: corrosive. Irritant effect on the eye: corrosive.

Sensitising effects

Based on available data, the classification criteria are not met.

no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 6 of 9

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Technically correct releases of minimal concentrations to adapted biological sewage treatment facility, will not disturb the biodegradability of activated sludge. due to the alkaline character of the product, usually, it has to be neutralized before contaminated effluents are introduced into the waste water treatment system.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1310-73-2	Sodium hydroxide; caustic soda					
	Acute fish toxicity	LC50 125 mg/l	96 h	Gambusia affinis	SDB Lieferant	
	Acute crustacea toxicity	EC50 40,4 mg/l	48 h	Ceriodaphnia	ECHA	
527-07-1	Sodium gluconate					
	Acute fish toxicity	LC50 >10000 mg/l	96 h			
100085-64-1	Cocobetainamido Amphopropionate					
	Acute fish toxicity	LC50 15 mg/l	96 h	Regenbogenforelle	OECD 203	
	Acute algae toxicity	ErC50 0,15 mg/l	72 h	Selenastrum capricornutum	OECD 201	
	Acute crustacea toxicity	EC50 4,4 mg/l	48 h	Daphnia magna	OECD 202	
	Acute bacteria toxicity	(EC50 >100 mg/l)		Belebtschlamm	OECD 209	

12.2. Persistence and degradability

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
527-07-1	Sodium gluconate			
		98 %	2	
100085-64-1	Cocobetainamido Amphopropionate			
	OECD 301A	>70 %	28	
	easily biodegradable			

12.3. Bioaccumulative potential

On the basis of existing data about disposal/decomposition and bio-accumulation potential, long term environmental damage is unlikely.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. not applicable

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 7 of 9

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

List of Wastes Code - used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packings can be re-cycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Other applicable information (land transport)

Excepted Quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Marine pollutant:	no
Special Provisions:	-
Limited quantity:	1 L
EmS:	F-A, S-B

Other applicable information (marine transport)

Excepted Quantity: E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN1824
14.2. UN proper shipping name:	SODIUM HYDROXIDE SOLUTION

TICKOPUR R 60

Revision date: 26.06.2023

No: 83028

Page 8 of 9

14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

Other applicable information (air transport)

Excepted Quantity: E2

Passenger-LQ: Y840

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): 0 % (0 g/l)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Data changed from previous versions: 1.1., 1.4., 2.1., 3.2., 7.1., 8.2., 9.1., 9.2., 11.1., 12.1., 12.2., 12.5., 12.6., 12.7., 15.1., 16.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data

Relevant H and EUH statements (number and full text)

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

Further Information

Training instructions: Notice the directions for use on the label.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

TICKOPUR R 60		
Revision date: 26.06.2023	No: 83028	Page 9 of 9

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	TICKOPUR R 60	IS, PW	0	35	8a, 9, 13	8a	0	26	

LCS: Life cycle stages
PC: Product categories
ERC: Environmental release categories
TF: Technical functions

SU: Sectors of use
PROC: Process categories
AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)